

Revision: 26.02.09 (Replaces 30.01.09) Grade name: VICTREX MSDS

SAFETY DATA SHEET ACCORDING TO EC-REGULATIONS 91/155/EEC, 2006/1907/EC and 2006/121/EC

1.IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE

COMPANY/UNDERTAKING

Identification of the substance or preparation:

VICTREX® 150G , 150GL15 , 150GL20 , 150GL30 , 450G 450GL15 , 450GL20 , 450GL30 , 90G , 90GL30 90GL60 , 650G

Company Identification:

Telephone: Fax: Emergency Phone No. Use of Substance / Preparation: Victrex Plc, Victrex Technology Centre, Hillhouse International, Thornton-Cleveleys, Lancs, FY5 4QD, UK

++ 44 (0) 1253 897700 ++ 44 (0) 1253 897701 ++ 44 (0) 1253 897754 The materials are generally used for injection moulding and extrusion operations. This material is not for human implantation.

2. HAZARDS IDENTIFICATION

EC Classification

Preparation is not classified as hazardous in the sense of directive 1999/45/EC and 2006/121/EC.

Product will burn in fire.

3.COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Preparation consisting of:

Polyetheretherketone (CAS No. 31694-16-3), Carbon fibres (CAS No. 7440-44-0).

HAZARDOUS INGREDIENT(S)	%W/W	CAS No.	EC No.	EC Classification
None.	-	-	-	-

For full text of R phrases see section 16.

4. FIRST AID MEASURES



4.1 Inhalation Remove patient from exposure. Keep patient at rest and give oxygen if breathing difficult. If symptoms develop, obtain medical attention. 4.2 Skin Contact After contact with skin, wash immediately with plenty of soap and water. In the event of contact with molten product: Cool affected area quickly with water. Do not attempt to remove hardened product. Obtain medical attention. 4.3 Eye Contact Irrigate with eyewash solution or clean water, holding the eyelids apart, for at least 15 minutes. If symptoms persist, obtain medical attention. 4.4 Ingestion May cause headache, nausea and vomiting. If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label. 4.5 Further Medical Treatment Unlikely to be required but if necessary treat symptomatically. 4.6 Special resources necessary for No data. first aid

VICTREX® Applications for higher strength and stiffness as well as high ductility. High performance thermoplastic material,glass fibre reinforced PolyEtherEtherKetone(PEEK)

5.F	IRE-FIGHTING MEASURES			
	Extinguishing Media	As appropriate for surrounding fire. Extinguish with carbon dioxide, dry chemical, foam or waterspray.		
5.3	Unsuitable Extinguishing Media Fire Fighting Protective upment	None known. Protective respirator with independent air supply. Full protection, if necessary.		
5.4	Special exposure hazards arising from the substance or preparation itself, combustion product, resulting gases. Other	In case of fire the following can develop: Oxides of carbon. Product will burn, but smoke emission is low. Dust is ignitable but will not sustain combustion. A high temperature source of ignition is required. Insensitive to sparks. The minimum spark energy required for ignition of a dust cloud is greater than 5000 mJ. It will not train fire, e.g. along beams etc. Dispose of contaminated extinction water according to official regulations.		
6. <i>4</i>	ACCIDENTAL RELEASE ME	ASURES		
	er to Section 13 and for personal pro Personal Precautions	tection refer to section 8 Avoid inhalation and contact with eyes or skin. Ensure sufficient supply of air. Avoid build up of dust. Remove possible cause of ignition – do not smoke. Take precautionary measures against static discharges.		
6.2 Environmental Exposure Controls 6.3 Methods for cleaning up		Avoid release to the environment. Prevent surface and ground water infiltration, as well as ground penetration. Collect mechanically and dispose of according to Section 13. Avoid build up of dust.		
7.H	ANDLING AND STORAGE			
7.1	HANDLING	See Section: 6.1 General hygiene measures for the handling of chemicals are applicable. When using do not smoke. Eating, drinking, smoking, as well as food storage, is prohibited in work room. Avoid build up of dust. Local Exhaust Ventilation at the workplace or on the processing machines required. Note: Danger of explosive dust. Machine Cleaning (purging): Purging with other polymers (e.g Polyethylene) at high temperatures can be hazardous. They may emit decomposition fumes which contain oxides of carbon and irritants. Auto ignition may also occur. Local exhaust ventilation is required. The relevant Safety Data Sheet for the purge material to be used should be consulted. Additional information can be obtained from the Victrex website www.victrex.com		
7.2	STORAGE	Requirements for storage rooms and containers: Not to be stored in gangways or stair wells. Store products enclosed, in original packing. Special storage conditions: See Section: 10.2. Store in dry place.		
	Storage Temperature: Storage Life: Specific use:	Ambient. Stable at ambient temperatures. Industrial use only.		

8.EXPOSURE CONTROLS/PERSONAL PROTECTION

Ensure adequate ventilation. This can be achieved by local exhaust ventilation or general ventilation. If this is insufficient to maintain the concentration under the WEL or TRGS 900 values, suitable breathing protection should be worn. Applies only if maximum permissible exposure values are listed here.

OCCUPATIONAL EXPOSURE LIMITS

SUBSTANCE.	CAS No.	LTEL (8 hr TWA ppm)	LTEL (8 hr TWA mg/m³)	STEL (ppm)	STEL (mg/m³)	Note:
Dust. (general dust limit value)	-		10			Inhalable Dust.
			4			Respirable Dust.
Fibre dust inorganic			2 fibres/ml,			
			5 mg/m3			

WEL: Workplace Exposure Limit (UK HSE EH40)

VICTREX® Applications for higher strength and stiffness as well as high ductility. High performance thermoplastic material,glass fibre reinforced PolyEtherEtherKetone(PEEK)

(P)	8.1 Respirators	If above exposure limits are likely to be exceeded, breathing mask with fine dust filter (EN 143)
	8.2 Eye Protection	Eye protection with side protection (EN 166)
	8.3 Gloves	Impervious Gloves. Plastic or synthetic rubber gloves. Additional information on hand protection – No tests have been performed. When dealing with heated material: Insulating gloves EN 407 (heat).
	8.4 Other	Protective working garments (e.g. safety shoes EN 344, long sleeved protective working garments).

9. PHYSICAL AND CHEMICAL PROPERTIES

Form Colour Odour pH (Value) Boiling Point (°C) Melting Point (°C) Flash Point (°C) Auto Ignition Temperature (°C) Explosive Properties Oxidising Properties Vapour Pressure (Pascal) Density (g/ml) Solubility (Water) Electrical properties Solid. (Granulate) Black. Odourless. Not known. Not known. 343 Not known. 595 May form explosible dust clouds in air. Not applicable. Not known. CA30~1.4 Insoluble. Contains carbon fibre. Dusts from this compound may be electrically conductive.

10. STABILITY AND REACTIVITY

10.1 Conditions to avoid

10.2 Materials to avoid 10.3 Hazardous Decomposition Product(s) See Section: 7. Stable when handled and stored correctly. Electrostatic charge. Open flame, ignition sources. Decomposes at temperatures above (°C): 450. See Section: 7. Concentrated Sulphuric acid. See Section: 5.4

11. TOXICOLOGICAL INFORMATION

The following information is based on a	a consideration of the properties of the main components of this mixture.
11.1 Ingestion	Predicted to be low toxicity under normal conditions of handling and use.
11.2 Inhalation	Mechanical irritation of the respiratory tract.
11.3 Skin Contact	Repeated and/or prolonged skin contact may cause irritation.
	In the event of contact with molten product: Thermal Burns (molten polymer will
	adhere to skin and cause severe burns).
11.4 Eye Contact	No data.Dust may have irritant effect on eyes. Permanent damage is unlikely.
11.5 Long Term Exposure	Chronic effects are unlikely.

12. ECOLOGICAL INFORMATION

12.1 Environmental Fate and Distribution	Insoluble in water. The product has low mobility in soil.
12.2 Persistence and Degradation	The substance is non biodegradable.
12.3 Toxicity	Low toxicity to aquatic organisms.
12.4 Effect on Effluent Treatment	Unlikely to affect biological treatment processes.
12.5 Water hazard class:	Not classified.

13. DISPOSAL CONSIDERATIONS

13.1 Regulatory information	Do not allow to enter drains, sewers or watercourses. Disposal should be in accordance with local, state or national legislation.
13.2 E.C disposal code no:	Allocation of a waste code number, according to the European Waste Catalogue, should be carried out in agreement with the regional waste disposal company. The waste codes are recommendations based on the scheduled use of this product. For alternative uses and applications, other waste codes may be allocated under certain circumstances. 07 02 13- waste plastic. 07 02 99- waste not otherwise specified.
13.3 Recommended:	Containers must be decontaminated in accordance with all applicable

VICTREX® Applications for higher strength and stiffness as well as high ductility. High performance thermoplastic material, glass fibre reinforced PolyEtherEtherKetone(PEEK)

regulations.

14. TRANSPORT INFORMATION

International Transport Regulations Not classified as dangerous for transport UN No.: Not applicable. **Road/Rail Transportation** Not applicable. (ADR/RID): Class/Packing Group: Not applicable. Classification code: Not applicable. LQ: Not applicable. EmS: Not applicable.

REGULATORY INFORMATION 15.

Classification according to Dangerous Product Regulations incl. EC Directives 67/548/EEC, 1999/45/EC and 2006/121/EC.

EC Classification Hazard Symbol **Risk Phrases** Safety Phrases **Observe restrictions** Not classified as dangerous for supply/use. Not applicable. Not applicable. Not applicable. VOC 1999/13/EC

INTERNATIONAL INVENTORIES

EINECS (Europe)

EINECS: Included.

16. OTHER INFORMATION

Manufactured in the UK under a Quality System approved to ISO 9001:2000 by Victrex Plc. This Safety Data Sheet was prepared in accordance with Directive 2001/58/EC. The following sections contain revisions or new statements: 1 - 16

GLOSSARY

WEL: Workplace Exposure Limit (UK HSE EH40) / Bmgv: Biological monitoring guidance value (UK HSE EH40) / EH40 -UK Occupational Exposure Limits.

Additional information on the properties, processing and application of VICTREX polymers is available at www.victrex.com. These details refer to the product as it is delivered.

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

World Headquarters

Victrex plc Hillhouse International Thornton Clevelevs Lancashire FY5 4OD United Kinadom Tel: + (44) 1253 897700 Fax: + (44) 1253 897701 Email: victrexplc@victrex.com

Americas Victrex USA Inc 300 Conshohocken State Road Suite 120 West Conshohocken, PA 19428 Germany USA Tel: + (1) 800-VICTREX Tel: + (1) 484-342-6001 Fax: + (1) 484-342-6002 Email: americas@victrex.com

Europe Victrex Europa GmbH Langgasse 16 65719 Hofheim/Ts. Tel: + (49) 6192 96490 Fax: + (49) 6192 964948 Email: eurosales@victrex.com

Asia Pacific Victrex Japan Inc Hanai Building 6F 1-2-9 Shiba-Kouen Minato-ku Tokvo 105-0011 Japan Tel: + (81) 35777 8737 Fax: + (81) 35777 8738 Email: japansales@victrex.com **Asia Pacific**

Victrex High Performance Materials (Shanghai) Co Ltd Part B Building G No. 1688 Zhuanxing Road Xinzhuang Industry Park Shanghai 201108 China Tel: + (86) 21-6113 6900 Fax: + (86) 21-6113 6901 Email: scsales@victrex.com